

GRABBER DA WB

ON/OFF-ROAD ALL POSITION



LEARN MORE



ALL-POSITION WIDE BASE TIRE
HIGH CARRYING CAPACITY AND
EXTRA-TOUGH TREAD ELEMENTS
TAKE THIS AGGRESSIVELY-
PATTERNED ALL POSITION TIRE TO
THE NEXT LEVEL OF SEVERE SERVICE
DURABILITY.

BUILT ON
PROVEN
PERFORMANCE



GENERAL TIRE

WWW.GENERALTIRETRUCK.COM

GRABBER OA WB

ON/OFF-ROAD ALL-POSITION



AGGRESSIVE MULTI-SERVICE, ALL-POSITION TREAD PATTERN

Aggressive multi-service, all-position tread pattern provides excellent traction in on/off road service.



CUT AND TEAR RESISTANT TREAD COMPOUND

Cut and tear resistant tread compound for long tread life in on/off road conditions.



TOUGH PENETRATION- RESISTANT CASING

Thick under tread resists casing penetration and damage allowing for multiple retreads.



MULTIPLE/EXTENSIVE USAGE APPLICATIONS

Construction service, on/off road, all-position.

APPLICATIONS: Construction Service, On/Off Highway, All-Position

| TIRE SIZE | LOAD RANGE | ARTICLE NUMBER | TREAD DEPTH (32nd) | MAX. SPEED MPH/ # | STATIC LOADED RADIUS IN (mm) | OVERALL INFLATED DIAMETER IN (mm) | OVERALL INFLATED WIDTH IN (mm) | LOADED SECTION WIDTH IN (mm) | APPROVED RIMS | MIN. DUAL SPACING IN (mm) | REVS. PER MILE (km) | TIRE WEIGHT LB (kg) | MAX LOAD@INFLATION | | | |
|--|------------|----------------|--------------------|-------------------|------------------------------|-----------------------------------|--------------------------------|------------------------------|---------------------|---------------------------|---------------------|---------------------|----------------------|------------------|--------------|----------------|
| | | | | | | | | | | | | | SINGLE LB (kg) | SINGLE PSI (kPa) | DUAL LB (kg) | DUAL PSI (kPa) |
| TUBELESS TIRES ON 15 DEGREE DROP CENTER RIMS | | | | | | | | | | | | | | | | |
| 385/65R22.5 | L | 05350140000 | 21 | 68 | 19.5 (495) | 42.4 (1077) | 15.3 (389) | 16.1 (409) | 11.75, 12.25 | NA | 488 (303) | 162 (73) | 9920 130 (4500 900) | NA | | |
| 425/65R22.5 | L | 05350120000 | 21 | 68 | 20.2 (514) | 44.3 (1124) | 16.6 (422) | 18.0 (457) | 12.25, 13.00, 14.00 | NA | 468 (291) | 181 (82) | 11400 120 (5150 830) | NA | | |
| 445/65R22.5 (Tread B) | L | 05350130000 | 21 | 68 | 20.8 (528) | 45.1 (1145) | 17.4 (441) | 18.6 (472) | 13.00, 14.00 | NA | 459 (285) | 198 (90) | 12800 130 (5800 900) | NA | | |

Note - Rim listed first is the measuring rim. Minimum Dual Spacing calculated without chains. # - Exceeding the lawful speed limit is neither recommended nor endorsed. Overall widths will change 0.1 inch (2.5 mm) for each 1/4 inch change in rim width. Minimum dual spacing should be adjusted accordingly. Continental Tire the Americas, LLC. reserves the right to change product specifications at any time without notice or obligations. Please consult rim manufacturers load and inflation limits. Never exceed rim manufacturers limits without permission of component manufacturer.