

# GRABBER DA WB

## ON/OFF-ROAD ALL POSITION



**ALL-POSITION WIDE BASE TIRE**  
HIGH CARRYING CAPACITY AND  
EXTRA-TOUGH TREAD ELEMENTS  
TAKE THIS AGGRESSIVELY-  
PATTERNED ALL POSITION TIRE TO  
THE NEXT LEVEL OF SEVERE SERVICE  
DURABILITY.

**BUILT ON**  
**PROVEN**  
**PERFORMANCE**



**GENERAL TIRE**

[WWW.GENERALTIRETRUCK.COM](http://WWW.GENERALTIRETRUCK.COM)

# GRABBER OA WB

## ON/OFF-ROAD ALL-POSITION



### AGGRESSIVE MULTI-SERVICE, ALL-POSITION TREAD PATTERN

Aggressive multi-service, all-position tread pattern provides excellent traction in on/off road service.



### CUT AND TEAR RESISTANT TREAD COMPOUND

Cut and tear resistant tread compound for long tread life in on/off road conditions.



### TOUGH PENETRATION- RESISTANT CASING

Thick under tread resists casing penetration and damage allowing for multiple retreads.



### MULTIPLE/EXTENSIVE USAGE APPLICATIONS

Construction service, on/off road, all-position.

**APPLICATIONS:** Construction Service, On/Off Highway, All-Position

TIRE SIZE	LOAD RANGE	ARTICLE NUMBER	TREAD DEPTH (32nd)	MAX. SPEED MPH/ #	STATIC LOADED RADIUS IN (mm)	OVERALL INFLATED DIAMETER IN (mm)	OVERALL INFLATED WIDTH IN (mm)	LOADED SECTION WIDTH IN (mm)	APPROVED RIMS	MIN. DUAL SPACING IN (mm)	REVS. PER MILE (km)	TIRE WEIGHT LB (kg)	MAX LOAD@INFLATION			
													SINGLE LB (kg)	SINGLE PSI (kPa)	DUAL LB (kg)	DUAL PSI (kPa)
TUBELESS TIRES ON 15 DEGREE DROP CENTER RIMS																
385/65R22.5	L	05350140000	21	68	19.5 (495)	42.4 (1077)	15.3 (389)	16.1 (409)	11.75, 12.25	NA	488 (303)	162 (73)	9920 130 (4500 900)	NA		
425/65R22.5	L	05350120000	21	68	20.2 (514)	44.3 (1124)	16.6 (422)	18.0 (457)	12.25, 13.00, 14.00	NA	468 (291)	181 (82)	11400 120 (5150 830)	NA		
445/65R22.5 (Tread B)	L	05350130000	21	68	20.8 (528)	45.1 (1145)	17.4 (441)	18.6 (472)	13.00, 14.00	NA	459 (285)	198 (90)	12800 130 (5800 900)	NA		

Note - Rim listed first is the measuring rim. Minimum Dual Spacing calculated without chains. # - Exceeding the lawful speed limit is neither recommended nor endorsed. Overall widths will change 0.1 inch (2.5 mm) for each 1/4 inch change in rim width. Minimum dual spacing should be adjusted accordingly. Continental Tire the Americas, LLC. reserves the right to change product specifications at any time without notice or obligations. Please consult rim manufacturers load and inflation limits. Never exceed rim manufacturers limits without permission of component manufacturer.