

GENERAL HT

HIGHWAY TRAILER



LEARN MORE



NEW LONG HAUL TRAILER TIRE
THIS SOLID SHOULDER TRAILER
TIRE OFFERS STONE EJECTION
TECHNOLOGIES AS WELL AS
INCREASED DURABILITY , LOW
ROLLING RESISTANCE AND A WIDER
CASING PLATFORM.

**BUILT ON
PROVEN
PERFORMANCE**



GENERAL TIRE

WWW.GENERALTIRETRUCK.COM

GENERAL HT

HIGHWAY TRAILER



IMPROVED PERFORMANCE TREAD PATTERN

New tread design provides proven fuel economy and performance in a demanding application.



INNOVATIVE STONE REPELLENT TREAD PATTERN

Patented groove technology leads to minimum stone retention and extended casing life.



REINFORCED DAMAGE-REDUCING SIDEWALL

Scruff ribs protect sidewall from curbing and cutting.



LOW ROLLING RESISTANCE

Tread compound reduces cost by optimizing fuel consumption.

APPLICATIONS: Long-Haul, Highway Trailer Axle

| TIRE SIZE | LOAD RANGE | ARTICLE NUMBER | TREAD DEPTH (32nds) | MAX. SPEED MPH # | STATIC LOADED RADIUS IN (mm) | OVERALL INFLATED DIAMETER IN (mm) | OVERALL INFLATED WIDTH IN (mm) | LOADED SECTION WIDTH IN (mm) | APPROVED RIMS | MIN. DUAL SPACING IN (mm) | REVS. PER MILE (km) | TIRE WEIGHT LB (kg) | MAX LOAD@INFLATION | | | |
|--|------------|----------------|---------------------|------------------|------------------------------|-----------------------------------|--------------------------------|------------------------------|---------------|---------------------------|---------------------|---------------------|---------------------|---------------------|--------------|----------------|
| | | | | | | | | | | | | | SINGLE LB (kg) | SINGLE PSI (kPa) | DUAL LB (kg) | DUAL PSI (kPa) |
| TUBELESS TIRES ON 15 DEGREE DROP CENTER RIMS | | | | | | | | | | | | | | | | |
| 11R22.5 | G | 05310400000 | 13 | 75 | 19.3 (490) | 41.1 (1044) | 11.1 (282) | 12.2 (310) | 8.25, 7.50 | 12.5 (318) | 504 (313) | 105 (48) | 6175 105 (2800 720) | 5840 105 (2650 720) | | |
| 255/70R22.5 | H | 05310420000 | 18 | 75 | 17.1 (434) | 36.6 (929) | 9.9 (251) | 10.8 (274) | 7.50, 8.25 | 11.3 (287) | 566 (352) | 91 (41) | 5510 120 (2500 830) | 5070 120 (2300 830) | | |
| 295/75R22.5 | G | 05310440000 | 13 | 75 | 18.5 (470) | 39.8 (1011) | 10.9 (277) | 12.0 (305) | 8.25, 7.50 | 12.5 (318) | 520 (323) | 100 (45) | 6175 110 (2800 760) | 5675 110 (2575 760) | | |
| 11R24.5 | G | 05310410000 | 13 | 75 | 20.2 (513) | 43.0 (1092) | 11.1 (282) | 12.2 (310) | 8.25, 7.50 | 12.5 (318) | 481 (299) | 113 (51) | 6610 105 (3000 720) | 6005 105 (2725 720) | | |
| 285/75R24.5 | G | 05310430000 | 13 | 75 | 19.1 (485) | 41.1 (1041) | 10.9 (277) | 12.0 (305) | 8.25 | 12.5 (318) | 505 (314) | 106 (48) | 6175 110 (2800 760) | 5675 110 (2575 760) | | |

Minimum Dual Spacing calculated without chains. # - Exceeding the lawful speed limit is neither recommended nor endorsed. Overall widths will change 0.1 inch (2.5 mm) for each 1/4 inch change in rim width. Minimum dual spacing should be adjusted accordingly. Continental Tire the Americas, LLC. reserves the right to change product specifications at any time without notice or obligations. Please consult rim manufacturers load and inflation limits. Never exceed rim manufacturers limits without permission of component manufacturer.