



GENERAL TIRE 

19.5" TRUCK TIRES

PRODUCT LINEUP

The **General RA 2 and RD 2*** are well-known and trusted tires delivering reliable performance in regional and on-/off-road applications.

**Formerly the previous generation Continental HSR+ and HDR+ 225/70R19.5-G.*

APPLICATIONS: REGIONAL, PICK-UP & DELIVERY, AND ON/OFF HIGHWAY

GENERAL TIRE. SINCE 1915.

GENERALTIRETRUCK.COM

19.5" TRUCK TIRES **PRODUCT LINEUP**



GENERAL **RA 2**

- Tread compounding designed to provide **durability and improved mileage**.
- Closed shoulder tread pattern provides **even wear and reduced noise**, while still delivering M+S rating.
- **Scuff rib** to protect against curbing, cuts and abrasions.
- Tread compounding designed for **improved mileage and durability**.
- 16/32nds all-position tread pattern **provides extended mileage** in regional, local service and off-road use.

M+S

MUD + SNOW RATED

TIRE SIZE	LOAD RANGE	ARTICLE NUMBER	TREAD DEPTH (32NDS)	MAX. SPEED (MPH)	STATIC LOADED RADIUS		OVERALL INFLATED DIAMETER		OVERALL INFLATED WIDTH		LOADED SECTION WIDTH		APPROVED RIM(S)	MIN. DUAL SPACING		REVS PER UNIT		TIRE WEIGHT		MAX. LOAD @ INFLATION	
					IN	MM	IN	MM	IN	MM	IN	MM		IN	MM	IN	MM	MI	KM	LBS	KG
225/70R19.5	G	05126710000	16	87	15.1	382	32.1	816	8.7	221	9.3	237	6.00, 6.75	10.0	254	644	400	63	29	3970 / 110 (1800 / 760)	3750 / 110 (1700 / 760)

TUBELESS TIRES ON 15 DEGREE DROP CENTER RIMS



GENERAL **RD 2**

- **Aggressive tread design** delivers traction in all weather conditions.
- **Open shoulder tread** designed with tie bar for traction and durability.
- 18/32nds tread pattern provides **excellent traction and long mileage** in regional, local service and on-/off-road conditions.
- Tread compounding designed to provide **increased mileage and durability**.

M+S

MUD + SNOW RATED

TIRE SIZE	LOAD RANGE	ARTICLE NUMBER	TREAD DEPTH (32NDS)	MAX. SPEED (MPH)	STATIC LOADED RADIUS		OVERALL INFLATED DIAMETER		OVERALL INFLATED WIDTH		LOADED SECTION WIDTH		APPROVED RIM(S)	MIN. DUAL SPACING		REVS PER UNIT		TIRE WEIGHT		MAX. LOAD @ INFLATION	
					IN	MM	IN	MM	IN	MM	IN	MM		IN	MM	IN	MM	MI	KM	LBS	KG
225/70R19.5	G	05225800000	18	87	15.1	384	32.2	819	8.7	221	9.4	238	6.00, 6.75	10.0	254	642	399	63	29	3970 / 110 (1800 / 760)	3750 / 110 (1700 / 760)

TUBELESS TIRES ON 15 DEGREE DROP CENTER RIMS

Note - Rim listed first is the measuring rim. ® = Intelligent Tire. Minimum Dual Spacing calculated without chains. # - Exceeding the lawful speed limit is neither recommended nor endorsed. Overall widths will change 0.1 inch (2.5 mm) for each 1/4 inch change in rim width. Minimum dual spacing should be adjusted accordingly. Continental Tire the Americas, LLC. reserves the right to change product specifications at any time without notice or obligations. Please consult rim manufacturer's load and inflation limits. Never exceed rim manufacturer's limits without permission of component manufacturer.