



TRUST BUILT BY THE MILE.

GENERAL HD

LONG/SHORT HAUL, DRIVE AXLE

- › MANY MILES TO REMOVAL
- › DURABLE COMPOUNDING
- › SUSTAINED TRACTION



GENERALTIRE




LONG / SHORT HAUL,
DRIVE AXLE

GENERAL HD

STONE EJECTOR

DURABLE COMPOUND




FEATURES & BENEFITS

Closed shoulder tread design delivers high mileage.

Deep 30/32" Tread with intermediate blocks deliver sustained traction in demanding applications.

Durable tread compounding to deliver cut & chip resistance and long tread life.

Stone ejection system reduces stone retention.



TECHNICAL DATA: GENERAL HD

TIRE SIZE	LOAD RANGE	ARTICLE NUMBER	TREAD DEPTH (32NDS)	MAX. SPEED (MPH)	STATIC LOADED RADIUS		OVERALL INFLATED DIAMETER		OVERALL INFLATED WIDTH		LOADED SECTION WIDTH		APPROVED RIM(S)	MIN. DUAL SPACING		REVS PER UNIT		TIRE WEIGHT		MAX. LOAD @ INFLATION	
					IN	MM	IN	MM	IN	MM	IN	MM		IN	MM	MI	KM	LBS	KG	SINGLE LBS, PSI (KG, KPa)	DUAL LBS, PSI (KG, KPa)
11R22.5	H	05210960000 05653870000	30	75	19.6	498	42.1	1069	11.1	282	12.3	312	8.25, 7.50	12.5	318	492	306	124	56	6610 / 120 3000 / 830	6005 / 120 2725 / 830
11R24.5	H	05210980000	30	75	20.6	523	44.1	1120	11.1	282	12.3	312	8.25, 7.50	12.5	318	469	292	133	60	7160 / 120 (3250 / 830)	6610 / 120 (3000 / 830)

TUBELESS TIRES ON 15 DEGREE DROP CENTER RIMS

■ STANDARD ARTICLE ■ INTELLIGENT ARTICLE

Note: Rim listed first is the measuring rim. Minimum Dual Spacing calculated without chains. These specifications subject to change without notice. # - Exceeding the lawful speed limit is neither recommended nor endorsed. Overall widths will change 0.1 inch (2.5 mm) for each 1/4 inch change in rim width. Minimum dual spacing should be adjusted accordingly. Continental Tire the Americas, LLC reserves the right to change product specifications at any time without notice or obligations. Please consult rim manufacturers load and inflation limits. Never exceed rim manufacturers limits without permission of component manufacturer.

***General MD 2 to replace General HD, Mid 2025**