



TRUST BUILT BY THE MILE.

GENERAL HS 2

LONG HAUL, HIGHWAY STEER POSITION



- › LONG DISTANCE HAULS
- › MANY MILES TO REMOVAL
- › FUEL-EFFICIENT
- › COMFORTABLE RIDE



GENERALTIRE




Smartway® Verified

LONG HAUL,
HIGHWAY STEER POSITION

GENERAL HS 2

NEW TREAD FOOTPRINT DELIVERS SIGNIFICANT WEAR IMPROVEMENT. 50% BETTER MILEAGE *

ADVANCED TREAD COMPOUND PROVIDES LOW ROLLING RESISTANCE FOR OPTIMAL FUEL EFFICIENCY



FEATURES & BENEFITS

Technologically advanced tread compound contributes to low rolling resistance for **optimum fuel efficiency**. Smartway verified.


Improved footprint delivers significant wear improvements for increased removal miles. **More than 50% mileage improvement.***

Shoulder and decoupler groove modifications add **enhanced durability for resistance to cuts and tears**.

Casing platform delivers **optimal performance & maximum retreadability**.

Enhanced bead to belt package increases casing durability for **maximum retreadability**.

*Improvement versus predecessor General HS.



TECHNICAL DATA: GENERAL HS 2

TIRE SIZE	LOAD RANGE	ARTICLE NUMBER	TREAD DEPTH (32NDS)	MAX. SPEED (MPH)	STATIC LOADED RADIUS		OVERALL INFLATED DIAMETER		OVERALL INFLATED WIDTH		LOADED SECTION WIDTH	APPROVED RIM(S)	MIN. DUAL SPACING		REVS PER UNIT		TIRE WEIGHT		MAX. LOAD @ INFLATION		
					IN	MM	IN	MM	IN	MM			IN	MM	IN	MM	MI	KM	LBS	KG	SINGLE LBS, PSI (KG, KPa)
11R22.5	H	05112020000 05653890000	19	75	19.5	495	41.5	1054	11.2	283	12.2	309	8.25, 7.50	12.5	318	499	310	118	53	6610 / 120 (3000 / 830)	6005 / 120 (2725 / 830)
295/75R22.5	H	05112030000 05653900000	19	75	18.8	477	40.3	1024	11.2	284	12.2	310	8.25, 9.00	12.5	318	514	319	115	52	7160 / 120 (3250 / 830)	6610 / 120 (3000 / 830)
11R24.5	H	05112040000 05653910000	19	75	20.4	518	43.5	1105	11.2	285	12.3	320	8.25, 7.50	12.5	318	476	296	126	57	7160 / 120 (3250 / 830)	6610 / 120 (3000 / 830)
285/75R24.5	H	05112050000 05653920000	19	75	19.5	495	41.5	1055	10.9	276	12.0	305	8.25, 7.50 9.00	12.5	318	498	310	119	54	6780 / 120 (3075 / 830)	6175 / 120 (2800 / 830)

TUBELESS TIRES ON 15 DEGREE DROP CENTER RIMS

■ STANDARD ARTICLE ■ INTELLIGENT ARTICLE

Note: Rim listed first is the measuring rim. Minimum Dual Spacing calculated without chains. These specifications subject to change without notice. # - Exceeding the lawful speed limit is neither recommended nor endorsed. Overall widths will change 0.1 inch (2.5 mm) for each 1/4 inch change in rim width. Minimum dual spacing should be adjusted accordingly. Continental Tire the Americas, LLC reserves the right to change product specifications at any time without notice or obligations. Please consult rim manufacturers load and inflation limits. Never exceed rim manufacturers limits without permission of component manufacturer.

GENERALTIRE.COM