



TRUST BUILT BY THE MILE.

GENERAL ST250 LP

LONG HAUL AND REGIONAL HAUL,
ON-/OFF-HIGHWAY, LOW PLATFORM TRAILER AXLE



- › LONG & SHORT DISTANCE HAULS
- › GREAT HANDLING
- › DURABLE TREAD COMPOUNDS




GENERAL TIRE



**LONG HAUL AND REGIONAL
HAUL, ON-/OFF-HIGHWAY,
LOW PLATFORM TRAILER AXLE**

**GROOVES PROVIDE
ENHANCED WET TRACTION**



GENERAL ST250 LP

FEATURES & BENEFITS

Unique grooves provide water evacuation contributing to **enhanced wet traction**.

Patented stone ejection system reduces stone retention and casing penetrations.



TECHNICAL DATA: GENERAL ST250 LP

TIRE SIZE	LOAD RANGE	ARTICLE NUMBER	TREAD DEPTH (32NDS)	MAX. SPEED (MPH)	STATIC LOADED RADIUS		OVERALL INFLATED DIAMETER		OVERALL INFLATED WIDTH		LOADED SECTION WIDTH	APPROVED RIM(S)	MIN. DUAL SPACING		REVS PER UNIT		TIRE WEIGHT		MAX. LOAD @ INFLATION		
					IN	MM	IN	MM	IN	MM			IN	MM	IN	MM	MI	KM	LBS	KG	SINGLE LBS, PSI (KG, KPa)
255/70R22.5	H	05681130000	16	75	16.9	429	36.5	927	9.8	249	11.0	279	8.25, 7.50	11.3	287	567	352	88	40	5510 / 120 (2500 / 830)	5070 / 120 (2300 / 830)

TUBELESS TIRES ON 15 DEGREE DROP CENTER RIMS

■ STANDARD ARTICLE

■ INTELLIGENT ARTICLE

Note: Rim listed first is the measuring rim. Minimum Dual Spacing calculated without chains. # - Exceeding the lawful speed limit is neither recommended nor endorsed. Overall widths will change 0.1 inch (2.5 mm) for each 1/4 inch change in rim width. Minimum dual spacing should be adjusted accordingly. Continental Tire the Americas, LLC reserves the right to change product specifications at any time without notice or obligations. Please consult rim manufacturers load and inflation limits. Never exceed rim manufacturers limits without permission of component manufacturer.