



**ON/OFF-ROAD APPLICATION**



# GRABBER OD

**CONSTRUCTION SERVICE, ON/OFF HIGHWAY,  
DRIVE POSITION**

## FOR MORE THAN 100 YEARS

General Tire offers robust and reliable truck tires that cover Highway, Regional, Urban and On/Off-Road applications for commercial vehicles. Whatever your application, you can trust General Tire to have your back.

GENERAL TIRE. SINCE 1915



**GENERAL TIRE**

[WWW.GENERALTIRETRUCK.COM](http://WWW.GENERALTIRETRUCK.COM)






ON/OFF-ROAD APPLICATION



# GRABBER OD

CONSTRUCTION SERVICE, ON/OFF HIGHWAY, DRIVE POSITION



## FEATURES & BENEFITS

- ▶ Deep, self-cleaning tread pattern with cut-resistant compound for long wear and extended mileage.
- ▶ Excellent traction in all weather conditions, both on and off-road.
- ▶ Sidewall profile resists curb damage, while groove technology reduces stone retention and drilling.



## TECHNICAL DATA

Tire Size	Load Range	Article Number	Tread Depth   32nds	Max Speed   MPH	Static Loaded Radius IN (MM)	Overall Inflated Diameter IN (MM)	Overall Inflated Width IN (MM)	Loaded Section Width IN (MM)	Approved Rim(s)	Minimum Dual Spacing IN (MM)	Revs Per Unit MI (KM)	Tire Weight LB (KG)	Single Max. Load @ Inflation LB PSI (KG, KPa)	Dual Max. Load @ Inflation LB PSI (KG, KPa)
11R22.5*	H	05250330000	30	68	19.6 (498)	42.3 (1074)	11.1 (282)	12.2 (310)	8.25, 7.50	12.5 (318)	489 (304)	128 (58)	6610 / 120 (3000 / 830)	6005 / 120 (2725 / 830)
11R24.5	H	05250340000	30	68	20.6 (524)	44.2 (1123)	11.1 (281)	12.2 (310)	8.25, 7.50	12.5 (318)	468 (291)	137 (62)	7160 / 120 (3250 / 830)	6610 / 120 (3000 / 830)

TUBELESS TIRES ON 15 DEGREE DROP CENTER RIMS

Note - Rim listed first is the measuring rim. Minimum Dual Spacing calculated without chains. \* - ECE Certified # - Exceeding the lawful speed limit is neither recommended nor endorsed. Overall widths will change 0.1 inch (2.5 mm) for each 1/4 inch change in rim width. Minimum dual spacing should be adjusted accordingly. Continental Tire the Americas, LLC. reserves the right to change product specifications at any time without notice or obligations. Please consult rim manufacturers load and inflation limits. Never exceed rim manufacturers limits without permission of component manufacturer.

01/2021 © Continental Tire the Americas, LLC CVT-GT-SS-GOD

