



HIGHWAY APPLICATION



GENERAL HT

LONG HAUL, HIGHWAY TRAILER AXLE

FOR MORE THAN 100 YEARS

General Tire offers robust and reliable truck tires that cover Highway, Regional, Urban and On/Off-Road applications for commercial vehicles. Whatever your application, you can trust General Tire to have your back.

GENERAL TIRE. SINCE 1915



GENERAL TIRE

WWW.GENERALTIRETRUCK.COM




HIGHWAY APPLICATION



GENERAL HT

LONG HAUL, HIGHWAY TRAILER AXLE



Smartway Verified



FEATURES & BENEFITS

- Tread design provides proven fuel economy and performance in a demanding application.
- Wider casing allows for industry standard 220mm retread.
- Patented innovative groove technology leads to minimum stone retention, extending casing life.
- Scruff ribs protect sidewall from curbing and cutting.
- 13/32" tread depth minimizes tread squirm and irregular wear.



TECHNICAL DATA

Tire Size	Load Range	Article Number	Tread Depth 32nds	Max Speed MPH	Static Loaded Radius IN (MM)	Overall Inflated Diameter IN (MM)	Overall Inflated Width IN (MM)	Loaded Section Width IN (MM)	Approved Rim(s)	Minimum Dual Spacing IN (MM)	Revs Per Unit MI (KM)	Tire Weight LB (KG)	Single Max. Load @ Inflation LB, PSI (KG, KPa)	Dual Max. Load @ Inflation LB, PSI (KG, KPa)
11R22.5	G	05310400000 # 05650990000 #	13	75	19.3 (490)	41.1 (1044)	11.1 (282)	12.2 (310)	8.25, 7.50	12.5 (318)	504 (313)	105 (48)	6175 / 105 (2800 / 720)	5840 / 105 (2650 / 720)
255/70R22.5*	H	05310420000 # 05650860000 #	18	75	17.1 (434)	36.6 (929)	9.9 (251)	10.8 (274)	7.50, 8.25	11.3 (287)	566 (352)	91 (41)	5510 / 120 (2500 / 830)	5070 / 120 (2300 / 830)
295/75R22.5	G	05310440000 # 05650920000 #	13	75	18.5 (470)	39.8 (1011)	10.9 (277)	12.0 (305)	8.25, 7.50	12.5 (318)	520 (323)	100 (45)	6175 / 110 (2800 / 760)	5675 / 110 (2575 / 760)
11R24.5	G	05310410000 # 05651030000 #	13	75	20.2 (513)	43.0 (1092)	11.1 (282)	12.2 (310)	8.25, 7.50	12.5 (318)	481 (299)	113 (51)	6610 / 105 (3000 / 720)	6005 / 105 (2725 / 720)
285/75R24.5	G	05310430000	13	75	19.1 (485)	41.1 (1041)	10.9 (277)	12.0 (305)	8.25	12.5 (318)	505 (314)	106 (48)	6175 / 110 (2800 / 760)	5675 / 110 (2575 / 760)

TUBELESS TIRES ON 15 DEGREE DROP CENTER RIMS

Note - Rim listed first is the measuring rim. # = Intelligent Tire. Minimum Dual Spacing calculated without chains. # - Exceeding the lawful speed limit is neither recommended nor endorsed. Overall widths will change 0.1 inch (2.5 mm) for each 1/4 inch change in rim width. Minimum dual spacing should be adjusted accordingly. Continental Tire the Americas, LLC. reserves the right to change product specifications at any time without notice or obligations. Please consult rim manufacturers load and inflation limits. Never exceed rim manufacturers limits without permission of component manufacturer.

