



REGIONAL/URBAN APPLICATION



GENERAL RD

**LONG/SHORT HAUL, HIGHWAY
SINGLE/TANDEM DRIVE AXLE**

FOR MORE THAN 100 YEARS

General Tire offers robust and reliable truck tires that cover Highway, Regional, Urban and On/Off-Road applications for commercial vehicles. Whatever your application, you can trust General Tire to have your back.

GENERAL TIRE. SINCE 1915



GENERAL TIRE

WWW.GENERALTIRETRUCK.COM





REGIONAL/URBAN APPLICATION



GENERAL RD

LONG/SHORT HAUL, HIGHWAY SINGLE/TANDEM DRIVE AXLE



FEATURES & BENEFITS

- An open shoulder drive tire that gives long life over short or long hauls with great traction.
- Innovative lug angle provides outstanding traction throughout the life of the tread.
- Tread design provides excellent wet/dry traction, resists irregular wear and reduces stone retention.



TECHNICAL DATA

Tire Size	Load Range	Article Number	Tread Depth 32nds	Max Speed MPH	Static Loaded Radius IN (MM)	Overall Inflated Diameter IN (MM)	Overall Inflated Width IN (MM)	Loaded Section Width IN (MM)	Approved Rim(s)	Minimum Dual Spacing IN (MM)	Revs Per Unit MI (KM)	Tire Weight LB (KG)	Single Max Load @ Inflation LB, PSI (KG, KPa)	Dual Max Load @ Inflation LB, PSI (KG, KPa)
11R22.5*	G	05211030000 # 05653170000 #	28	75	19.5 (495)	41.8 (1062)	11.3 (287)	12.1 (307)	8.25	12.5 (318)	495 (308)	120 (54)	6175 / 105 (2800 / 720)	5840 / 105 (2650 / 720)
11R22.5*	H	05211040000 # 05653180000 #	28	75	19.5 (495)	41.8 (1062)	11.3 (287)	12.1 (307)	8.25	12.5 (318)	495 (308)	122 (55)	6610 / 120 (3000 / 830)	6005 / 120 (2725 / 830)
295/75R22.5*	G	05211080000	28	75	18.9 (480)	40.8 (1036)	11.0 (279)	12.2 (310)	8.25	12.5 (318)	508 (315)	114 (52)	6175 / 110 (2800 / 760)	5675 / 110 (2575 / 760)
11R24.5	G	05211050000 # 05653190000 #	28	75	20.6 (523)	43.8 (1113)	11.3 (287)	12.2 (310)	8.25	12.5 (318)	473 (294)	128 (58)	6610 / 105 (3000 / 720)	6005 / 105 (2725 / 720)
11R24.5	H	05211060000 # 05653200000 #	28	75	20.6 (523)	43.8 (1113)	11.3 (287)	12.2 (310)	8.25	12.5 (318)	473 (294)	131 (59)	7160 / 120 (3250 / 830)	6610 / 120 (3000 / 830)
285/75R24.5	G	05211070000	28	75	19.6 (498)	42.0 (1066)	10.7 (273)	12.1 (307)	8.25	12.5 (318)	493 (306)	118 (53)	6175 / 110 (2800 / 760)	5675 / 110 (2575 / 760)

TUBELESS TIRES ON 15 DEGREE DROP CENTER RIMS

Note - Rim listed first is the measuring rim. # = Intelligent Tire. Minimum Dual Spacing calculated without chains. # - Exceeding the lawful speed limit is neither recommended nor endorsed. Overall widths will change 0.1 inch (2.5 mm) for each 1/4 inch change in rim width. Minimum dual spacing should be adjusted accordingly. Continental Tire the Americas, LLC. reserves the right to change product specifications at any time without notice or obligations. Please consult rim manufacturers load and inflation limits. Never exceed rim manufacturers limits without permission of component manufacturer.

