

# GRABBER™

# A/T<sup>X</sup>

ALL-TERRAIN STUDDABLE, SYMMETRIC

THE GRABBER A/T<sup>X</sup> IS A NEXT-GENERATION, AGGRESSIVE ALL-TERRAIN TIRE THAT PROVIDES EXCEPTIONAL OFF-ROAD CAPABILITY AND DURABILITY, BALANCED WITH IMPRESSIVE ON-ROAD PERFORMANCE. THREE-PEAK MOUNTAIN SNOWFLAKE AND STUDDABILITY DELIVER CONFIDENT DRIVING IN ALL WEATHER CONDITIONS.

**DURAGEN™ Technology:** Robust design and materials provide long, even wear and excellent cut and chip durability.

**StabiliTread™ Technology:** A larger footprint and optimized pattern stiffness promote even wear and long tread life.

**ComfortBalance™ Technology:** A tread cushioning system with acoustic tread pattern provides a more comfortable, quiet ride.

**Snowflake Approved and Studdable Design:** Provides excellent performance in all weather conditions and features Three-Peak Mountain Snowflake marking and studdability.



UTQG:	TREAD WEAR:	TRACTION:	TEMPERATURE:
METRIC SIZES	640	A	B



Available in Raised White Letter (RWL) and Black Sidewall (BSW).

Excludes all LT Metric and Flotation sizes

**60**  
THOUSAND MILE  
LIMITED TREADWEAR WARRANTY

Includes all LT Metric and Flotation sizes

**50**  
THOUSAND MILE  
LIMITED TREADWEAR WARRANTY

**45**  
DAY TRIAL  
OR THE FIRST 2/32<sup>nds</sup> OF TREAD

See warranty manual for complete detail on Limited Warranty and Limited Trial.



Meets the severe snow service requirements of the U.S. Tire Manufacturers Association (USTMA) and the Tire and Rubber Association of Canada (TRAC).

Size	Load/Speed	Load Range	Sidewall	Article Number	Rim Protect	Tire Diameter (in)	Tire Weight (lbs)	MAX. PSI	Approved Rim Width (in)	MAX. Load (lbs)	Tread Depth (in - 32nds)	Revs Per Mile
27 X 8.50 R 14 LT	95 Q	C	RWL	04508120000	Yes	26.9	30.1	50	(6.0 - 7.5)	1,521	16	1484
30 X 9.50 R 15 LT	104 S	C	RWL	04508400000	Yes	30.0	37.1	50	(6.5 - 8.5)	1,984	16	1385
31 X 10.50 R 15 LT	109 S	C	RWL	04508420000	Yes	31.0	44.0	50	(7.0 - 9.0)	2,271	16	1385
33 X 12.50 R 15 LT	108 R	C	RWL	04508430000	Yes	33.0	53.2	35	(8.5 - 11.0)	2,205	16	1385
35 X 12.50 R 15 LT	113 Q	C	RWL	04508410000	Yes	35.0	59.8	35	(8.5 - 11.0)	2,535	16	1385
LT 235/75 R 15	104/101 S	C	RWL	04508390000	Yes	28.9	35.2	50	(6.0 - 7.0)	1,984	16	719
225/75 R 16	108 T	XL	RWL	04508450000	Yes	29.3	32.2	51	(6.0 - 7.5)	2,205	14	709
LT 235/85 R 16	120/116 S	E	RWL	04508440000	Yes	31.7	49.0	80	(6.0 - 7.5)	3,086	16	655
LT 245/75 R 16	120/116 R	E	RWL	04508460000	Yes	30.5	46.8	80	(6.5 - 8.0)	3,086	16	682
LT 265/75 R 16	123/120 R	E	RWL	04508470000	Yes	31.6	51.9	80	(7.0 - 8.0)	3,415	16	656
LT 285/75 R 16	126/123 R	E	RWL	04508480000	Yes	32.8	58.1	80	(7.5 - 9.0)	3,750	16	633
LT 305/70 R 16	124/121 R	E	RWL	04508500000	Yes	32.8	60.2	65	(8.0 - 9.5)	3,525	16	633
LT 315/75 R 16	127/124 R	E	RWL	04508490000	Yes	34.6	64.6	65	(8.0 - 11.0)	3,860	16	600
265/70 R 17	115 T	SL	RWL	04508380000	Yes	31.6	41.4	44	(7.0 - 9.0)	2,679	14	657
35 X 12.50 R 17 LT	121 R	E	RWL	04508320000	Yes	35.0	64.6	65	(8.5 - 11.0)	3,195	16	1222
37 X 12.50 R 17 LT	124 R	D	RWL	04508330000	Yes	37.0	69.7	50	(8.5 - 11.0)	3,525	16	1222
LT 235/80 R 17	120/117 R	E	BSW	04508510000	Yes	31.8	46.4	80	(6.0 - 7.5)	3,086	16	653
LT 245/70 R 17	119/116 S	E	RWL	04508530000	Yes	30.5	49.4	80	(6.5 - 8.0)	2,998	16	681
LT 245/75 R 17	121/118 S	E	RWL	04508520000	Yes	31.5	48.7	80	(6.5 - 7.5)	3,195	16	660
LT 265/70 R 17	121/118 S	E	RWL	04508370000	Yes	31.6	51.8	80	(7.0 - 8.5)	3,195	16	657
LT 275/70 R 17	121/118 R	E	RWL	04508360000	Yes	32.2	56.1	80	(7.0 - 8.5)	3,195	16	646
LT 285/70 R 17	121/118 S	E	RWL	04508350000	Yes	32.7	57.5	80	(7.5 - 9.0)	3,195	16	635
LT 315/70 R 17	121/118 S	E	RWL	04508340000	Yes	34.4	65.2	65	(8.0 - 11.0)	3,195	16	605
35 X 12.50 R 18 LT	123 R	E	RWL	04508240000	Yes	35.0	64.9	65	(8.5 - 11.0)	3,415	16	1154
LT 265/70 R 18	124/121 S	E	RWL	04508310000	Yes	32.6	54.0	80	(7.0 - 9.0)	3,525	16	637
LT 275/65 R 18	123/120 R	E	RWL	04508290000	Yes	32.1	55.8	80	(7.5 - 9.0)	3,415	16	648
LT 275/70 R 18	125/122 R	E	RWL	04508300000	Yes	33.2	58.1	80	(7.0 - 8.5)	3,640	16	627
LT 285/60 R 18	122/119 S	E	BSW	04508250000	Yes	31.5	54.5	80	(8.0 - 10.0)	3,305	16	660
LT 285/65 R 18	125/122 S	E	RWL	04508270000	Yes	32.6	56.2	80	(8.0 - 10.0)	3,640	16	637
305/50 R 20	120 T	XL	BSW	04508150000	Yes	32.0	48.9	51	(8.5 - 11.0)	3,086	14	649
33 X 12.50 R 20 LT	114 S	E	BSW	04508130000	Yes	33.0	62.4	65	(8.5 - 11.0)	2,601	16	1039
35 X 12.50 R 20 LT	121 R	E	BSW	04508140000	Yes	35.0	68.4	65	(8.5 - 11.0)	3,195	16	1039
LT 265/60 R 20	121/118 S	E	BSW	04508220000	Yes	32.5	57.4	80	(7.5 - 9.5)	3,195	16	639
LT 275/55 R 20	115/112 T	D	BSW	04508180000	Yes	31.9	54.1	65	(7.5 - 9.5)	2,679	15	651
LT 275/60 R 20	119/116 S	D	BSW	04508210000	Yes	33.0	56.3	65	(7.5 - 9.5)	2,998	16	630
LT 275/65 R 20	126/123 S	E	BSW	04508230000	Yes	34.1	60.7	80	(7.5 - 9.5)	3,750	16	610
LT 285/55 R 20	117/114 T	D	BSW	04508170000	Yes	32.3	58.7	65	(8.0 - 10.0)	2,833	15	642
LT 285/60 R 20	125/122 S	E	BSW	04508200000	Yes	33.5	60.7	80	(8.0 - 10.0)	3,640	16	621
LT 305/55 R 20	121/118 S	E	BSW	04508160000	Yes	33.2	60.6	65	(8.5 - 11.0)	3,195	16	626
LT 325/60 R 20	126 S	E	BSW	04508190000	Yes	35.4	71.0	65	(9.0 - 12.0)	3,750	16	588

RWL = Raised White Letter  
BSW = Black Sidewall

Stud Length: 12 mm (TSMI #13)