




## GRABBER OD

CONSTRUCTION SERVICE, ON/OFF HIGHWAY, DRIVE POSITION







## **FEATURES & BENEFITS**

- ▶ Deep, self-cleaning tread pattern with cut-resistant compound for long wear and extended mileage.
- Excellent traction in all weather conditions, both on and off-road.
- Sidewall profile resists curb damage, while groove technology reduces stone retention and drilling.

TECHNICAL DATA															To T
(	\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\	1000 Range	Aricle Number	Tread Dean	Max Speed	Static Coded	Over all make	Overall Infat	Logo Section Section	Approved Rims)	W Com	Rey Per Unit	Tire Weight	/0/	0000 (6.5%) (7.1%) (8.5%) (8.1
	11R22.5*	Н	05250330000	30	68	19.6 (498)	42.3 (1074)	11.1 (282)	12.2 (310)	8.25, 7.50	12.5 (318)	489 (304)	128 (58)	6610 / 120 (3000 / 830)	6005 / 120 (2725 / 830)
	11R24.5	Н	05250340000	30	68	20.6 (524)	44.2 (1123)	11.1 (281)	12.2 (310)	8.25, 7.50	12.5 (318)	468 (291)	137 (62)	7160 / 120 (3250 / 830)	6610 / 120 (3000 / 830)
						TURFI FS	S TIRES OF	V 15 DEG	REE DRO	P CENTER RIN	/S				

Note - Rim listed first is the measuring rim. Minimum Dual Spacing calculated without chains. \* - ECE Certified # - Exceeding the lawful speed limit is neither recommended nor endorsed. Overall widths will change 0.1 inch (2.5 mm) for each 1/4 inch change in rim width. Minimum dual spacing should be adjusted accordingly. Continental Tire the Americas, LLC. reserves the right to change product specifications at any time without notice or obligations. Please consult rim manufacturers load and inflation limits. Never exceed rim manufacturers limits without permission of component manufacturer.

