



TRUST BUILT BY THE MILE.

GENERAL HD 2

LONG HAUL, HIGHWAY TANDEM DRIVE AXLE



- › LONG DISTANCE HAULS
- › MANY MILES TO REMOVAL
- › FUEL-EFFICIENT
- › COMFORTABLE RIDE



GENERAL TIRE

GENERAL TIRE. SINCE 1915

GENERALTIRETRUCK.COM



SMARTWAY® VERIFIED

LONG HAUL, HIGHWAY TANDEM DRIVE AXLE GENERAL HD 2

CLOSED SHOULDER DESIGN PROVIDES EVEN WEAR

LOW ROLLING RESISTANCE FOR MAXIMIZED FUEL EFFICIENCY



FEATURES & BENEFITS

New advanced tread compound provides **IMPROVED MILEAGE AND DURABILITY.***


LOW ROLLING RESISTANCE for great maximized fuel economy. Smartway Verified.

28/32" TREAD DEPTH for extended tire life.

CLOSED SHOULDER TREAD DESIGN provides even tread wear and enhanced wet traction.

Patented innovative groove technology leads to **MINIMUM STONE RETENTION**, extending casing life.

**IMPROVEMENT VERSUS PREDECESSOR GENERAL HD.*



TECHNICAL DATA

TIRE SIZE	LOAD RANGE	ARTICLE NUMBER	TREAD DEPTH (32NDS)	MAX. SPEED (MPH)	STATIC LOADED RADIUS		OVERALL INFLATED DIAMETER		OVERALL INFLATED WIDTH		LOADED SECTION WIDTH		APPROVED RIM(S)	MIN. DUAL SPACING		REVS PER UNIT		TIRE WEIGHT		MAX. LOAD @ INFLATION	
					IN	MM	IN	MM	IN	MM	IN	MM		IN	MM	IN	MM	MI	KM	LBS	KG
11R22.5	G	05211770000 *0565350000*	28	75	19.6	498	42.0	1067	11.1	282	12.1	307	8.25, 7.50	12.5	318	493	306	123	56	6175 / 105 2800 / 720	5840 / 105 2650 / 720
295/75R22.5	G	05211790000 *05653520000*	28	75	18.9	481	40.7	1034	11.0	279	12.0	304	8.25, 9.00	12.5	318	509	316	115	52	6175 / 110 (2800 / 760)	5675 / 110 (2575 / 760)
11R24.5	G	05211800000 *05653530000*	28	75	20.6	523	44.0	1118	11.1	282	12.1	307	8.25, 7.50	12.5	318	470	292	132	60	6610 / 105 (3000 / 720)	6005 / 105 (2725 / 720)
285/75R24.5	G	05211830000 *05653550000*	28	75	19.6	498	42.0	1067	10.7	272	12.1	307	8.25, 7.50	12.5	318	493	306	121	55	6175 / 110 (2800 / 760)	5675 / 110 (2575 / 760)

TUBELESS TIRES ON 15 DEGREE DROP CENTER RIMS

Note - Rim listed first is the measuring rim. * = Intelligent Tire Article #. Minimum Dual Spacing calculated without chains. # - Exceeding the lawful speed limit is neither recommended nor endorsed. Overall widths will change 0.1 inch (2.5 mm) for each 1/4 inch change in rim width. Minimum dual spacing should be adjusted accordingly. Continental Tire the Americas, LLC. reserves the right to change product specifications at any time without notice or obligations. Please consult rim manufacturers load and inflation limits. Never exceed rim manufacturers limits without permission of component manufacturer.

Whether your operation is highway, regional, urban or on/off-road, **you can trust General Tire to deliver commercial truck tires that work as hard as you do.**

GENERALTIRETRUCK.COM