



HIGHWAY APPLICATION



GENERAL HT+

LONG HAUL, HIGHWAY TRAILER AXLE

FOR MORE THAN 100 YEARS

General Tire offers robust and reliable truck tires that cover Highway, Regional, Urban and On/Off-Road applications for commercial vehicles. Whatever your application, you can trust General Tire to have your back.

GENERAL TIRE. SINCE 1915



GENERAL TIRE

WWW.GENERALTIRETRUCK.COM




HIGHWAY APPLICATION



GENERAL HT+

LONG HAUL, HIGHWAY TRAILER AXLE



Smartway Verified



FEATURES & BENEFITS

- Advanced tread compound delivers **20% mileage improvement*** and **ultra low rolling resistance**.
- Improved compounds with superior tear resistance for **15% more cut/chip/chunk resistance***.
- Self-cleaning tread design and groove geometry **prevents stone trapping** for extended casing life.
- Superior bead and belt package for casing durability and **maximum retreadability**.

*Improvement versus predecessor General HT.



TECHNICAL DATA

TECHNICAL DATA																
Tire Size	Load Range	Article Number	Tread Depth 32nds		Max Speed MPH	Static Loaded Radius IN (MM)	Overall Inflated Radius IN (MM)	Overall Inflated Diameter IN (MM)	Loaded Inflated Width IN (MM)	Loaded Section Width IN (MM)	Approved Rim(s)	Minimum Dual Spacing IN (MM)	Revs Per Unit MI (KM)	Tire Weight LB (KG)	Single Max. Load @ Inflation LB, PSI (KG, KPa)	Dual Max. Load @ Inflation LB, PSI (KG, KPa)
11R22.5	G	05310670000	13	75	19.3 (490)	41.1 (1044)	11.1 (282)	12.2 (310)	8.25, 7.50	12.5 (318)	504 (313)	105 (48)	6175 / 105 (2800 / 720)	5840 / 105 (2650 / 720)		
255/70R22.5*	H	05310680000	18	75	17.1 (434)	36.6 (929)	9.9 (251)	10.8 (274)	7.50, 8.25	11.3 (287)	566 (352)	91 (41)	5510 / 120 (2500 / 830)	5070 / 120 (2300 / 830)		
295/75R22.5	G	05310690000	13	75	18.5 (470)	39.8 (1011)	10.9 (277)	12.0 (305)	8.25, 7.50	12.5 (318)	520 (323)	100 (45)	6175 / 110 (2800 / 760)	5675 / 110 (2575 / 760)		
11R24.5	G	05310700000	13	75	20.2 (513)	43.0 (1092)	11.1 (282)	12.2 (310)	8.25, 7.50	12.5 (318)	481 (299)	113 (51)	6610 / 105 (3000 / 720)	6005 / 105 (2725 / 720)		
285/75R24.5	G	05310710000	13	75	19.1 (485)	41.1 (1041)	10.9 (277)	12.0 (305)	8.25	12.5 (318)	505 (314)	106 (48)	6175 / 110 (2800 / 760)	5675 / 110 (2575 / 760)		
TIRELESS TIRES ON 15 DEGREE DROP CENTER RIMS																

TUBELESS TIRES ON 15 DEGREE DROP CENTER RIMS

Note - Rim listed first is the measuring rim. Minimum Dual Spacing calculated without chains. # - Exceeding the lawful speed limit is neither recommended nor endorsed. Overall widths will change 0.1 inch (2.5 mm) for each 1/4 inch change in rim width. Minimum dual spacing should be adjusted accordingly. Continental Tire the Americas, LLC, reserves the right to change product specifications at any time without notice or obligations. Please consult rim manufacturers load and inflation limits. Never exceed rim manufacturers limits without permission of component manufacturer.

