



TRUST BUILT BY THE MILE.

GENERAL HT+

LONG HAUL, FUEL EFFICIENT TRAILER TIRE



- › LONG DISTANCE HAULS
- › MANY MILES TO REMOVAL
- › FUEL-EFFICIENT
- › COMFORTABLE RIDE



GENERAL TIRE

GENERAL TIRE. SINCE 1915

GENERALTIRETRUCK.COM




SMARTWAY VERIFIED

LONG HAUL, FUEL EFFICIENT TRAILER TIRE

GENERAL HT+

20% MILEAGE IMPROVEMENT*
DUE TO ADVANCED COMPOUND

ULTRA LOW ROLLING RESISTANCE
PROVIDES MAXIMUM FUEL EFFICIENCY



FEATURES & BENEFITS

Advanced tread compound delivers **20% MILEAGE IMPROVEMENT***


ULTRA LOW ROLLING RESISTANCE, Smartway and GHG 2 (Greenhouse Gas Phase II) compliant.

Improved compounds with superior tear resistance for **15% MORE CUT/CHIP/CHUNK RESISTANCE.***

Self-cleaning tread design and groove geometry **PREVENTS STONE TRAPPING** for extended casing life.

Superior bead and belt package for casing durability and **MAXIMUM RETREADABILITY.**

**IMPROVEMENT VERSUS PREDECESSOR GENERAL HT.*



TECHNICAL DATA

TIRE SIZE	LOAD RANGE	ARTICLE NUMBER	TREAD DEPTH (32NDS)	MAX. SPEED (MPH)	STATIC LOADED RADIUS		OVERALL INFLATED DIAMETER		OVERALL INFLATED WIDTH		LOADED SECTION WIDTH	APPROVED RIM(S)	MIN. DUAL SPACING		REVS PER UNIT		TIRE WEIGHT		MAX. LOAD @ INFLATION		
					IN	MM	IN	MM	IN	MM			IN	MM	IN	MM	IN	MM	IN	MM	SINGLE LBS, PSI (KG, KPA)
11R22.5	G	05310670000 *05653700000*	13	75	19.3	490	41.1	1044	11.1	282	12.2	310	8.25, 7.50	12.5	318	504	313	106	48	6175 / 105 (2800 / 720)	5840 / 105 (2650 / 720)
295/75R22.5	G	05310690000 *05653720000*	13	75	18.5	470	39.8	1011	10.9	277	12.0	305	8.25, 7.50	12.5	318	520	323	100	45	6175 / 110 (2800 / 760)	5675 / 110 (2800 / 760)
11R24.5	G	05310700000 *05653730000*	13	75	20.2	513	43.0	1092	11.1	282	12.2	310	8.25, 7.50	12.5	318	481	299	114	52	6610 / 105 (3000 / 720)	6005 / 105 (2725 / 720)
285/75R24.5	G	05310710000 *05653740000*	13	75	19.1	485	41.1	1044	10.9	277	12.0	305	8.25	12.5	318	504	313	104	47	6175 / 110 (2800 / 760)	5675 / 110 (2575 / 760)
255/70R22.5	H	05310680000 *05653710000*	18	75	16.5	420	36.6	930	9.9	251	10.3	262	6.75, 7.50, 8.25	11.3	287	566	351	90	41	5510 / 120 (2500 / 830)	5070 / 120 (2300 / 830)

TUBELESS TIRES ON 15 DEGREE DROP CENTER RIMS

Note - Rim listed first is the measuring rim. ** = Intelligent Tire Article #. Minimum Dual Spacing calculated without chains. # - Exceeding the lawful speed limit is neither recommended nor endorsed. Overall widths will change 0.1 inch (2.5 mm) for each 1/4 inch change in rim width. Minimum dual spacing should be adjusted accordingly. Continental Tire the Americas, LLC. reserves the right to change product specifications at any time without notice or obligations. Please consult rim manufacturers load and inflation limits. Never exceed rim manufacturers limits without permission of component manufacturer.

Whether your operation is highway, regional, urban or on/off-road, **you can trust General Tire to deliver commercial truck tires that work as hard as you do.**

GENERALTIRETRUCK.COM