



TRUST BUILT BY THE MILE.

GENERAL MD 2

REGIONAL LONG/SHORT HAUL, DRIVE AXLE



- › HIGH REMOVAL MILES
- › DURABLE COMPOUNDING
- › SUSTAINED TRACTION



GENERALTIRE




LONG / SHORT HAUL,
DRIVE AXLE

GENERAL MD 2

STONE BUMPER

DURABLE COMPOUND



FEATURES & BENEFITS


Trusted performance thanks to the General HD legacy.

Durable Compound & Deep 30/32" Tread design for superior mileage, traction and durability.

Versatile and dependable, designed to handle multiple applications with ease.

Consistent performance in all weather conditions due to closed shoulder tread design.

Stone bumpers to protect casing life.



TECHNICAL DATA: GENERAL MD 2

TIRE SIZE	LOAD RANGE	ARTICLE NUMBER	TREAD DEPTH (32NDS)	MAX. SPEED (MPH)	STATIC LOADED RADIUS		OVERALL INFLATED DIAMETER		OVERALL INFLATED WIDTH		LOADED SECTION WIDTH		APPROVED RIM(S)	MIN. DUAL SPACING		REVS PER UNIT		TIRE WEIGHT		MAX. LOAD @ INFLATION	
					IN	MM	IN	MM	IN	MM	IN	MM		IN	MM	MI	KM	LBS	KG	SINGLE LBS, PSI (KG, KPa)	DUAL LBS, PSI (KG, KPa)
11R22.5	H	05212470000 05656130000	30	75	19.6	498	42.1	1069	11.1	282	12.3	312	8.25, 7.50	12.5	318	492	306	124	56	6610 / 120 3000 / 830	6005 / 120 2725 / 830
11R24.5	H	05212480000 05656140000	30	75	20.6	523	44.1	1120	11.1	282	12.3	312	8.25, 7.50	12.5	318	469	292	133	60	7160 / 120 (3250 / 830)	6610 / 120 (3000 / 830)

TUBELESS TIRES ON 15 DEGREE DROP CENTER RIMS

■ STANDARD ARTICLE

■ INTELLIGENT ARTICLE

Note: Rim listed first is the measuring rim. Minimum Dual Spacing calculated without chains. These specifications subject to change without notice. # - Exceeding the lawful speed limit is neither recommended nor endorsed. Overall widths will change 0.1 inch (2.5 mm) for each 1/4 inch change in rim width. Minimum dual spacing should be adjusted accordingly. Continental Tire the Americas, LLC reserves the right to change product specifications at any time without notice or obligations. Please consult rim manufacturers load and inflation limits. Never exceed rim manufacturers limits without permission of component manufacturer.