



TRUST BUILT BY THE MILE.

GENERAL RA 2

19.5" ALL-POSITION IN REGIONAL HAULING,
PICK-UP & DELIVERY, AND ON-/OFF-HIGHWAY

- › CLOSED SHOULDER TREAD PATTERN PROVIDES EVEN WEAR AND REDUCED NOISE
- › COMPOUNDING DESIGNED WITH DURABILITY AND IMPROVED MILEAGE IN MIND



GENERALTIRE



19.5" ALL-POSITION
REGIONAL, PICK-UP & DELIVERY,
AND ON-/OFF-HIGHWAY

GENERAL RA 2

M+S

Mud + Snow Designation

TREAD COMPOUNDING DESIGNED
TO PROVIDE DURABILITY AND
IMPROVED MILEAGE




FEATURES & BENEFITS

Closed shoulder tread pattern provides **even wear and reduced noise**, while still delivering M+S designation.

Scuff rib to protect against curbing, cuts and abrasions.

Tread compounding designed for **improved mileage and durability**.

16/32nds all-position tread pattern **provides extended mileage** in regional, local service and off-road use.



TECHNICAL DATA

TIRE SIZE	LOAD RANGE	ARTICLE NUMBER	TREAD DEPTH (32NDS)	MAX. SPEED (MPH)	STATIC LOADED RADIUS		OVERALL INFLATED DIAMETER		OVERALL INFLATED WIDTH		LOADED SECTION WIDTH		APPROVED RIM(S)	MIN. DUAL SPACING		REVS PER UNIT		TIRE WEIGHT		MAX. LOAD @ INFLATION	
					IN	MM	IN	MM	IN	MM	IN	MM		IN	MM	MI	KM	LBS	KG	SINGLE LBS, PSI (KG, KPa)	DUAL LBS, PSI (KG, KPa)
225/70R19.5	G	05126710000 05655030000	16	87	15.1	382	32.1	816	8.7	221	9.3	237	6.00, 6.75	10.0	254	644	400	63	29	3970 / 110 (1800 / 760)	3750 / 110 (1700 / 760)

TUBELESS TIRES ON 15 DEGREE DROP CENTER RIMS

■ STANDARD ARTICLE

■ INTELLIGENT ARTICLE

Note: Rim listed first is the measuring rim. Minimum Dual Spacing calculated without chains. # - Exceeding the lawful speed limit is neither recommended nor endorsed. Overall widths will change 0.1 inch (2.5 mm) for each 1/4 inch change in rim width. Minimum dual spacing should be adjusted accordingly. Continental Tire the Americas, LLC reserves the right to change product specifications at any time without notice or obligations. Please consult rim manufacturers load and inflation limits. Never exceed rim manufacturers limits without permission of component manufacturer.