



TRUST BUILT BY THE MILE.

GENERAL RD 2

19.5" ALL-POSITION IN REGIONAL HAULING,
PICK-UP & DELIVERY, AND ON/OFF HIGHWAY

- › COMPOUNDING DESIGNED WITH DURABILITY AND IMPROVED MILEAGE IN MIND
- › AGGRESSIVE TREAD DESIGN DELIVERS TRACTION IN ANY WEATHER CONDITION



GENERAL TIRE



19.5" DRIVE SERVICE
IN REGIONAL HAULING,
PICK-UP & DELIVERY,
AND ON/OFF HIGHWAY

GENERAL RD 2

AGGRESSIVE TREAD DESIGN
DELIVERS TRACTION IN ALL
WEATHER CONDITIONS




FEATURES & BENEFITS

OPEN SHOULDER TREAD designed with tie bar for traction and durability

18/32" tread pattern provides **EXCELLENT TRACTION AND LONG MILEAGE** in regional, local service and on/off road conditions

Tread compounding designed to provide **INCREASED MILEAGE AND DURABILITY**



TECHNICAL DATA

| TIRE SIZE | LOAD RANGE | ARTICLE NUMBER | TREAD DEPTH (32NDS) | MAX. SPEED (MPH) | STATIC LOADED RADIUS | | OVERALL INFLATED DIAMETER | | OVERALL INFLATED WIDTH | | LOADED SECTION WIDTH | | APPROVED RIM(S) | MIN. DUAL SPACING | | REVS PER UNIT | | TIRE WEIGHT | | MAX. LOAD @ INFLATION | |
|-------------|------------|------------------------------|---------------------|------------------|----------------------|-----|---------------------------|-----|------------------------|-----|----------------------|-----|-----------------|-------------------|-----|---------------|-----|-------------|----|----------------------------|----------------------------|
| | | | | | IN | MM | IN | MM | IN | MM | IN | MM | | IN | MM | MI | KM | LBS | KG | SINGLE LBS, PSI (KG, KPA) | DUAL LBS, PSI (KG, KPA) |
| 225/70R19.5 | G | 05225800000 *05655040000* | 18 | 87 | 15.1 | 384 | 32.2 | 819 | 8.7 | 221 | 9.4 | 238 | 6.00, 6.75 | 10.0 | 254 | 642 | 399 | 63 | 29 | 3970 / 110 (1800 / 760) | 3750 / 110 (1700 / 760) |

TUBELESS TIRES ON 15 DEGREE DROP CENTER RIMS

Note - Rim listed first is the measuring rim. * = Intelligent Tire. Minimum Dual Spacing calculated without chains. # - Exceeding the lawful speed limit is neither recommended nor endorsed. Overall widths will change 0.1 inch (2.5 mm) for each 1/4 inch change in rim width. Minimum dual spacing should be adjusted accordingly. Continental Tire the Americas, LLC. reserves the right to change product specifications at any time without notice or obligations. Please consult rim manufacturer's load and inflation limits. Never exceed rim manufacturer's limits without permission of component manufacturer.

Whether your operation is highway, regional, urban or on/off-road, **you can trust General Tire to deliver commercial truck tires that work as hard as you do.**

GENERALTIRETRUCK.COM