



TRUST BUILT BY THE MILE.

GENERAL RD 2

19.5" ALL-POSITION IN REGIONAL HAULING,
PICK-UP & DELIVERY, AND ON-/OFF-HIGHWAY



- › COMPOUNDING DESIGNED WITH DURABILITY AND IMPROVED MILEAGE IN MIND
- › AGGRESSIVE TREAD DESIGN DELIVERS TRACTION IN ANY WEATHER CONDITION



GENERAL TIRE



19.5" DRIVE REGIONAL,
PICK-UP & DELIVERY,
AND ON-/OFF-HIGHWAY

GENERAL RD 2

M+S

Mud + Snow Designation

AGGRESSIVE TREAD DESIGN DELIVERS TRACTION IN ALL WEATHER CONDITIONS




FEATURES & BENEFITS

Open shoulder tread designed with tie bar for traction and durability.

18/32nds tread pattern provides **excellent traction and long mileage** in regional, local service and on/off road conditions.

Tread compounding designed to provide **increased mileage and durability.**



TECHNICAL DATA: GENERAL RD 2

TIRE SIZE	LOAD RANGE	ARTICLE NUMBER	TREAD DEPTH (32NDS)	MAX. SPEED (MPH)	STATIC LOADED RADIUS		OVERALL INFLATED DIAMETER		OVERALL INFLATED WIDTH		LOADED SECTION WIDTH		APPROVED RIM(S)	MIN. DUAL SPACING		REVS PER UNIT		TIRE WEIGHT		MAX. LOAD @ INFLATION			
					IN	MM	IN	MM	IN	MM	IN	MM		IN	MM	IN	MM	MI	KM	LBS	KG	SINGLE LBS, PSI (KG, kPa)	DUAL LBS, PSI (KG, kPa)
225/70R19.5	G	05225800000 05655040000	18	87	15.1	384	32.2	819	8.7	221	9.4	238	6.00, 6.75	10.0	254	642	399	63	29	3970 / 110 (1800 / 760)	3750 / 110 (1700 / 760)		

TUBELESS TIRES ON 15 DEGREE DROP CENTER RIMS

■ STANDARD ARTICLE ■ INTELLIGENT ARTICLE

Note: Rim listed first is the measuring rim. Minimum Dual Spacing calculated without chains. # - Exceeding the lawful speed limit is neither recommended nor endorsed. Overall widths will change 0.1 inch (2.5 mm) for each 1/4 inch change in rim width. Minimum dual spacing should be adjusted accordingly. Continental Tire the Americas, LLC reserves the right to change product specifications at any time without notice or obligations. Please consult rim manufacturers load and inflation limits. Never exceed rim manufacturers limits without permission of component manufacturer.