

TRUST BUILT BY THE MILE.

## GENERAL RD

LONG/SHORT HAUL, HIGHWAY SINGLE/TANDEM DRIVE AXLE



- **GREAT HANDLING**
- > DURABLE TREAD COMPOUNDS







GENERAL TIRE. SINCE 1915 GENERALTIRETRUCK.COM








OPEN SHOULDER TREAD DESIGN PROVIDES GREAT TRACTION

STONE BUMPERS MINIMIZE STONE RETENTION




## **GENERAL RD**

## **FEATURES & BENEFITS**

An OPEN SHOULDER DRIVE tire that gives long life over short or long hauls with great traction.

Innovative lug angle provides OUTSTANDING TRACTION throughout the life of the tread.

Tread design provides excellent wet/dry traction, RESISTS IRREGULAR WEAR and reduces stone retention.



## **TECHNICAL DATA**

TIRE	LOAD	ARTICLE	TREAD	MAX.	STATIC LOADED RADIUS		OVERALL INFLATED DIAMETER		OVERALL INFLATED WIDTH		LOADED SECTION WIDTH		APPROVED RIM(S)	MIN. DUAL SPACING		REVS PER UNIT		TIRE WEIGHT		MAX. LOAD @ INFLATION	
SIZE	RANGE	NUMBER	DEPTH (32NDS)	SPEED (MPH)																SINGLE LBS. PSI	DUAL LBS, PSI
					IN	MM	IN	ММ	IN	ММ	IN	MM		IN	MM	MI	KM	LBS	KG	(KG, KPA)	(KG, KPA)
11R22.5	Н	05211040000 <b>0565318000</b> 0	28	75	19.5	495	41.8	1062	11.3	287	12.1	307	8.25	12.5	318	495	308	122	55	6610 / 120 (3000 / 830)	6005 / 120 (2725 / 830)
295/75R22.5	G	05211080000	28	75	18.9	480	40.8	1036	11.0	279	12.2	310	8.25	12.5	318	508	315	114	52	6175 / 110 (2800 / 760)	5675 / 110 (2575 / 760)
11R24.5	Н	05211060000 <b>05653200000</b> %	28	75	20.6	523	43.8	1113	11.3	287	12.2	310	8.25	12.5	318	473	294	131	59	7160 / 120 (3250 / 830)	6610 / 120 (3000 / 830)
285/75R24.5	G	05211070000	28	75	19.6	498	42.0	1066	10.7	273	12.1	307	8.25	12.5	318	493	306	118	53	6175 / 110 (2800 / 760)	5675 / 110 (2575 / 760)
					TII	RELE!	SS TII	RES O	N 15	DEGE	PEF D	RUB	CENTER RIP	MS							

Note - Rim listed first is the measuring rim. • • = Intelligent Tire. Minimum Dual Spacing calculated without chains. # - Exceeding the lawful speed limit is neither recommended nor endorsed. Overall widths will change 0.1 inch (2.5 mm) for each 1/4 inch change in rim width. Minimum dual spacing should be adjusted accordingly. Continental Tire the Americas, LLC. reserves the right to change product specifications at any time without notice or obligations. Please consult rim manufacturer's load and inflation limits. Never exceed rim manufacturer's limits without permission of component manufacturer.

Whether your operation is highway, regional, urban or on/off-road, you can trust General Tire to deliver commercial truck tires that work as hard as you do.