



TRUST BUILT BY THE MILE.

# GENERAL WT

WASTE TRANSPORT AND OTHER  
HIGH SCRUB, URBAN APPLICATIONS

- › LONG & SHORT DISTANCE  
HAULS
- › GREAT HANDLING
- › DURABLE TREAD  
COMPOUNDS



**GENERALTIRE**




WASTE TRANSPORT AND  
OTHER HIGH SCRUB,  
URBAN APPLICATIONS

# GENERAL WT

GROOVE TECHNOLOGY LEADS TO  
MINIMUM STONE RETENTION

COMPOUND PROVIDES RESISTANCE TO  
ABRASION, CUTTING AND CHIPPING




## FEATURES & BENEFITS

Advanced tread compound balances **cut and tear resistance** with optimized mileage specifically for the waste transport industry.

Bead construction engineered to withstand high brake temperatures, providing **structural durability** and extended product life.

Innovative groove technology leads to **minimum stone retention**, extending casing life.



## TECHNICAL DATA: GENERAL WT

TIRE SIZE	LOAD RANGE	ARTICLE NUMBER	TREAD DEPTH (32NDS)	MAX. SPEED (MPH)	STATIC LOADED RADIUS		OVERALL INFLATED DIAMETER		OVERALL INFLATED WIDTH		LOADED SECTION WIDTH		APPROVED RIM(S)	MIN. DUAL SPACING		REVS PER UNIT		TIRE WEIGHT		MAX. LOAD @ INFLATION	
					IN	MM	IN	MM	IN	MM	IN	MM		IN	MM	MI	KM	LBS	KG	SINGLE LBS, PSI (KG, KPa)	DUAL LBS, PSI (KG, KPa)
315/80R22.5	L	05323030000 05655660000	26	68	20.1	510	43.0	1093	12.5	316	13.6	345	9.00, 9.75	13.8	351	481	299	163	74	10,000 / 130 (4540 / 900)	9090 / 130 (4125 / 900)

TUBELESS TIRES ON 15 DEGREE DROP CENTER RIMS

■ STANDARD ARTICLE ■ INTELLIGENT ARTICLE

Note: Rim listed first is the measuring rim. Minimum Dual Spacing calculated without chains. # - Exceeding the lawful speed limit is neither recommended nor endorsed. Overall widths will change 0.1 inch (2.5 mm) for each 1/4 inch change in rim width. Minimum dual spacing should be adjusted accordingly. Continental Tire the Americas, LLC reserves the right to change product specifications at any time without notice or obligations. Please consult rim manufacturers load and inflation limits. Never exceed rim manufacturers limits without permission of component manufacturer.